

Technical Datasheet



tasker® C128 AR - 2x0,35 mm²

Balanced Armored Microphone Cable – Outdoor Use



A	B	C	D	E	F
---	---	---	---	---	---

CATEGORY

Balanced Microphone Cable (See Audio Catalogue)

APPLICATIONS

Outdoor and Underground Audio and Microphones installation.

- A:** Anti rodents **Metallic Armor** specific for Outdoor and underground installation, even in presence of rodents. Outer Diam. Ø 7,30 (±0,20) mm.
- B:** Black Soft **Flame Retardant PVC** - Outer Diam. Ø 6,30 (±0,20) mm.
- C:** Braided Shielding in O.F.C. tinned copper covering 90% .
- D:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- E:** Transparent Cores Insulation with compact PE. Diam. Ø 1,70 (±0,20) mm.
- F:** One conductor in O.F.C. red copper and one in O.F.C. tinned copper formation 11x0,20 mm. Nom. Cross section 2x0,35 mm².

MARKING

tasker® C128 AR– 2x0,35 mm² - Armored Balanced Microphone Cable - Made in Italy

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PVC**, **PUR**, With or without metallic armor.

Cable Properties

Conductor Resistance	58 Ω/Km
Capacity Core/Core	55 pF/mt
Capacity Core/Shield	92 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			